



DHS BRAKE KITS: PARTS DIAGRAMS AND SET-UP INFORMATION



COMPLETE DHS FLOATING BRAKE KIT, HAYES



COMPLETE DHS FLOATING BRAKE KIT, SHIMANO/ISO 8" ROTOR

All DHS Models (Mono & Tube) use a similar floating brake kit, with different brake arms/mounts for Hayes MC74 and Shimano style mounts. The Foes DHS floating brake system is intended for 8" rotors, and 6" rotors are not compatible. With the correct mount, both Hayes and Shimano calipers will bolt directly without adapters. International standard calipers that normally use a 6" rotor will also use the Shimano/ISO 8" rotor mount; just mount an 8" rotor in place of the 6". Important note: The Hayes MC74 brake arm/mount includes a "shear plate" to help relieve the forces applied to the bolt under braking. This is due to limited thread engagement, and therefore the shear plate is not needed when using the Shimano/ISO brake arm. See owners manual for installation tips.

HAYES MOUNT INCLUDES
EXTRA BOLT AND
SHEAR PLATE
(SEE MANUAL)



DHS BRAKE ARMS: HAYES (MC74) ON LEFT
AND SHIMANO (ISO 8" ROTOR) ON RIGHT



DHS BRAKE KITS: PARTS DIAGRAMS AND SET-UP INFORMATION



DHS REAR HUB ASSEMBLY, ALL MODELS

Pictured above is the proper hub axle arrangement for all DHS models. Remember to tighten axle securely when installing the wheel. Check that this is secure before every ride!